

ZEN Industries shop standards for rectangular duct

BASED ON 3rd Edition 2005 SMACNA STANDARDS

TDF - 1" W.G.

MAX. WIDTH	CONNECTOR	DUCT LENGTHS				
		60"	48"	36"	30"	24"
10" - DOWN	FS/D	26	26	26	26	26
11 - 12"	FS/D	26	26	26	26	26
13 - 14"	FS/D	26	26	26	26	26
15 - 16"	FS/D	26	26	26	26	26
17 - 18"	TDF	26	26	26	26	26
19 - 20"	TDF	26	26	26	26	26
21 - 22"	TDF	26	26	26	26	26
23 - 24"	TDF	26	26	26	26	26
25 - 26"	TDF	26	26	26	26	26
27 - 28"	TDF	26	26	26	26	26
29 - 30"	TDF	26	26	26	26	26
31 - 36"	TDF	26	26	26	26	26
37 - 42"	TDF	24	24	26	26	26
43 - 48"	TDF	22	24	24	24	26
49 - 54"	TDF	22	22	24	24	24
55 - 60"	TDF	24 MPT	22	22	24	24
61 - 72"	TDF	22 MPT	22 MPT	22	22	22
		20		20	20	
73 - 84"	TDF	MPT/JTR	20 MPT	MPT	MPT	22 MPT
				20	20	
85 - 96"	TDF	20 - 2MPT	20 - 2MPT	MPT	MPT	22 MPT
97 - 108"	WARD "J"	18 MPT	18 MPT	18	18	18
109 - 120"	WARD "J"	18 MPT	18 MPT	18	18	18

Zen Industries Standards based on the latest SMACNA standards:

galvanized sheets	26 & 24 ga	G-60 LFQ	22 to 18ga	G-90 LFQ
all duct 12" and above will be beaded				
1/2"wg. to 2"w.g	snaplock seam	(pittsburg available at an additional cost)		
3"wg up to 48"wide	snaplock seam	(duct over 48" wide-pittsburg)		
4"wg to 10"wg	pittsburg seam			
fittings - assembled	straight duct - unassembled	(assembly available at an additional cost)		
duct sections width + height	up to 18"	wrapped		
	up to 70"	"L" shaped		
	71" & up	4 pc.		
FS/D = flat slip(24ga) & drive(24ga)	ST-S/D = standing slip(22ga) & drive	TDF =T-25b roll formed flange		
	JTR= joint tie-rods			
MPT= midpoint tie-rod				
2x2x1/8" angle =	midpoint reinforcement in lieu of tie-rods			
Duct liner available 1/2" or 1"				

Sales & Estimating: Drew McCaffrey • Drew.McCaffrey@ZENIndustries.com • 877-600-0274 • Fax: 877-826-7952

Regional Sales Manager: Al Burling • al.burling@zenindustries.com • 517-290-1050

Accounting & Billing: Kim Zenisek • Kim@ZENIndustries.com • 888-415-4822 • Fax: 216-432-3241

ZEN Industries, Inc. • 2340 East 69th Street, Unit #2 • P.O. Box 604394 • Cleveland, OH 44104